FireAngel. 200 CONNECTED

FP2620W2-R BATTERY POWERED WIRELESS INTERLINK SMOKE ALARM

Sensor typeThermoptek Thermally Enhanced OpticalBattery type10 year sealed for life Panasonic lithium



- Connects directly to the **FireAngel Connect Gateway**, providing enhanced diagnostic capabilities and realtime notifications to mobile devices
- Thermoptek Thermally Enhanced Optical technology as used by over 90% of the UK Fire and Rescue Services
- Remote, automated reporting of buzzer status via FireAngel Connect
- Intelligent status monitoring without intrusive standby indicator LED
- Easily accessible central button to for Test / Smart Silence / Locate functions
- Smart Silence allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound
- Locate feature when the network goes into alarm pressing the test button of any alarm will silence all but the initiating alarm
- Can interlink with any Wi-Safe 2 compatible device including **FireAngel Connect Gateway**

Technical Specification

Dimensions	132mm (diameter) x 40.50mm (depth)
Supply voltage	3VDC
Battery	10 year sealed for life Panasonic lithium
Technology	Thermoptek and Wi-Safe 2
Alarm sound level	85dB(A) at 3m (minimum)
Installation positions	Wall / Ceiling
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	20°C to +60°C
Storage humidity	Up to 93% RH non-condensing
Plastic material	ABS, UL94 VO fire retardant
Warranty	5 years
Weight	210g
Certified to	EN14604:2005+AC:2008
Independently tested to	EN 300 220-2 V2.4.1, EN 301 489-3 V1.6.1, EN 301 489-1 V1.9.2
Maximum number of connected units	50 Wi-Safe 2 units
Operating frequency	868 MHz
Range	35m (over 200m in clear air)

FireAngel Connect

Monitor and manage multiple devices wherever you are with FireAngel Connect







