

Mains Powered Smoke Alarms FH250 Series

FH250BB (6 years)

Alkaline battery back-up (3xAAA)

FH250RB (10 years)

Rechargeable Lithium cell back-up



The range of **Fast-Fix** optical smoke alarms comes with our unique **X-Profile** photoelectric chamber, controlled by bespoke software and featuring **TSE-Technology** (Thermal Stability Enhancement), specifically designed to reduce nuisance alarms while maximising the detection of smoke and fire.

- Sealed-in rechargeable lithium cell back-up.
- Unique **X-Profile** detection chamber controlled by bespoke software.
- **TSE-Technology** (Thermal Stability Enhancement) provides stability across a range of environmental conditions, reducing nuisance alarms whilst enhancing detection.
- **ALARM SILENCE BUTTON**. Ideal in non-emergency situations (nuisance alarms).
- **SILENCE LOW BATTERY WARNING** chirp for up to 10 hours. Maintains continuous protection during sleeping hours
- **TEST BUTTON**. Extra large for ease of use.



EN14604:2005

Fast-Fix

- **NEW Fast-Fix** design simplifies fixing and wiring of the baseplate.
- **NEW** push fit wiring connection - fast and secure.
- Install the base first, then install the alarm later, after all the works have been completed, preventing contamination by dust, paint etc.
- Smoke and heat alarms share the same base allowing interchangeability.
- Dedicated and discrete entry for surface mounted trunking.

