

Model: 660MBX 230V Thermally enhanced optical smoke alarm

The 660MBX is a mains powered thermally enhanced optical smoke alarm with 9V alkaline battery back-up. Thermally enhanced optical technology combines very latest in optical sensing with a thermal enhancement, providing fast reaction to both slow smouldering and fast flaming fires in a single alarm.



Product features:

- 230V mains powered smoke alarm
- 9V alkaline battery back-up
- Thermally enhanced optical technology reduces nuisance alarms
- Test and alarm pause button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke and heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS EN 14604: 2005

Model number	660MBX
Description	230V smoke with alkaline battery bk-up
Technology	Thermally enhanced optical
Sensitivity	N/A
Alarm sound level	85db at 3 metres
Battery type	9V PP3 Alkaline
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	5°C (40°F) to 38°C (100°F)
Operating humidity	10% to 85% relative
Storage temperature	5°C (40°F) to 38°C (100°F)
Storage humidity	10% to 85% relative
Warranty	5 years

Dimensions - Alarm	140mm (D) x 44mm (H)
Unit weight - Alarm	224g
Pack dimensions	141mm (H) x 141mm (W) x 48mm (D)
Pack weight	TBC
Master pack quantity	10
Master pack dimensions	TBC
Master pack weight	TBC
Pack barcode	5022391065289
Outer barcode	15022391065286
Approvals	BS EN 14604: 2005