

Compliance Made Easy

# Freedor Pro

Freedor Pro takes the weight out of heavy fire doors and allows you to place them open at any angle with its free-swing feature.



## Overview

Freedor Pro is controlled by radio signal from the ProHub, meaning that in the event of a fire Freedor Pro will allow the doors to close, preventing the spread of smoke and fire.

ProHub is a separate controller which can be directly connected to any fire alarm panel.

## Features

- Place doors open at any angle with free-swing
- Connects to ProHub or ProExtender
- Easily monitor all units with Site Manager\*
- Hassle-free installation
- 2 year warranty

## Product Dimensions

	Width	320mm
	Height	70mm (105 mm with arm)
	Depth	95mm (120mm with disc)
	Weight	~4.5 kg

\*Subscription to InSite required.

## Specification Overview

Power	9v Alkaline battery pack
Warranty	2 years
Colour	Gloss: Silver, Brass, White. Matte: Black
Casing	Acrylic
Activation	Radio signal (433-434 MHz)
Radio range	Typical internal range 30-40m
Free-swing adjustment range	Pull-side: 90° +/- 20°, Push-side: 90° +/- 5°
Maximum door size	Power size 3 (maximum of 60kg and 950mm width)
Audible warning	Yes
Fire rating	Freedor has been tested to EN1634-1 on FD30 doorsets, exposed and unexposed faces.
Compliant to	EN1155:1997+A1:2002, EN1634-1:2014+A1:2018, EMC Directive, Radio Equipment Directive, CE Marked, UKCA Marked
Classification	Suitable for Critical (category A) under BS 7273-4:2015+A1:2021
Installation position	Top of door
Part number	<b>338-0604</b> Freedor Pro Silver Finish <b>170-2053</b> Freedor Pro Brass Finish <b>218-7342</b> Freedor Pro White Finish <b>408-1075</b> Freedor Pro Black Finish