

# K10SCO

## Combination Smoke and Carbon Monoxide Alarm

### Battery-Powered

#### Overview

---

Battery-powered combination alarm that offers protection from the dangers of smoke/fire and carbon monoxide.

The voice warning feature helps to determine which danger has been detected.



#### Key Features

---

- **Voice alarm feature** – tells you which danger has been detected
- **Peak level memory** – provides notification when dangerous CO levels have been detected
- **Front-load battery compartment** – quick and easy to change batteries without having to remove the alarm from the wall or ceiling
- **Green, amber and red LED's** indicate alarm status
- **End of life warning** alerts user to replace alarm after 10 years
- **Hush feature** – allows nuisance alarms to be temporarily silenced, such as those caused by cooking or steam
- **Test and reset button** to enable regular testing of alarm function
- **Battery operated** – 2 x AA alkaline batteries supplied as standard

# 10-year Carbon Monoxide Alarm with Digital Display

## Battery-Powered

### Technical Specifications

#### General

Model	K10SCO
Sensor Technology (CO)	Electrochemical
Sensor Technology (Smoke)	Optical
Primary Power Supply	2 x AA Batteries (Supplied)
Sound Output Level	85dB (A) at 3 metres (minimum)
Mounting Options	Wall or ceiling
End of Life Warning	Alerts user to replace after a minimum 10-years
Operating Temperature Range	-10°C to 40°C
Humidity Range	Up to 90% RH (non-condensing)
Storage and Transport	-20 °C to 60 °C, 5% to 95% RH (non-condensing)

#### Weights and Dimensions

Alarm Dimensions	145mm x 145mm x 45mm
Alarm Weight (including batteries)	360g
Case Quantity	6 units


#### Certification / Approvals

---

EN 14604:2005

EN 50291-1:2018

Manufactured to ISO9001 Standard



#### Warranty

---

10- Year manufacturer's warranty



©2023 Carrier - All Rights Reserved