

40 YEARS OF QUALITY BRITISH MANUFACTURING




ORBIX



EDEN

IP65 COMPACT BULKHEAD
PRODUCT DATA SHEET



PRODUCT DATA SHEET

EDEN

IP65 COMPACT BULKHEAD




IMAGES

- A Standard surface mounting Eden.
- B Eden fitted with semi-recessing trim (suffix **/ED/WH**).
- C Eden fitted with self-adhesive legend kit (suffix **/SAL1**).

FEATURES


- Soft arc linear diffuser designed to provide maximum spacings between emergency luminaires.
- IP65 flame retardant polycarbonate enclosure (white base/clear diffuser) and screw-fixing diffuser located with brass threaded inserts.
- Can be fitted with a self-adhesive legend kit to create an exit sign.
- High output options suitable for high bay applications.
- TM-21 L70 greater than 54,000 hours using 0.5W 150 lumen/Watt LEDs.
- CRI 80 (minimum).
- 3 step MacAdam rated.
- 4000K colour temperature as standard (2700K - 6500K available to order).



**TÜV RHEINLAND
CERTIFIED OPTION
AVAILABLE**

CATALOGUE NUMBERS & INFORMATION

MAINS LUMINAIRES			MAINS LUMENS			EMERGENCY LUMENS		
CAT NO	WATTS	WEIGHT	ECONOMY OUTPUT	STANDARD OUTPUT	HIGH OUTPUT			
ED/LED	3.5W	1.20Kg		150				
ED/LEDH	6W	1.20Kg			342			

EMERGENCY LUMINAIRES			MAINS LUMENS			EMERGENCY LUMENS		
CAT NO	WATTS	WEIGHT	ECONOMY OUTPUT	STANDARD OUTPUT	HIGH OUTPUT	ECONOMY OUTPUT	STANDARD OUTPUT	HIGH OUTPUT
ED/LED/M3 	7.5W	1.45Kg		120			120	
ED/LEDH/M3H	6W	1.45Kg			200			200
ED/LED/NM3H	7W	1.20Kg						305
ED/LEDH/C3	13W	1.45Kg			342		120	
ED/LEDH/C3H	13W	1.45Kg			342			305

CENTRAL SYSTEM SLAVE LUMINAIRES				MAINS LUMENS			EMERGENCY LUMENS		
CAT NO	W	VA	WEIGHT	ECONOMY OUTPUT	STANDARD OUTPUT	HIGH OUTPUT	ECONOMY OUTPUT	STANDARD OUTPUT	HIGH OUTPUT
ED/LED/LVR24	4	3	1.20Kg		150			135	
ED/LED/LVR50	4	3	1.20Kg		150			135	
ED/LED/LVR110	4	3	1.20Kg		150			135	
ED/LED/LVR220	4	3	1.20Kg		150			135	
ED/LED/24D	4	3	1.20Kg					135	
ED/LED/50D	4	3	1.20Kg					135	
ED/LED/110D	4	3	1.20Kg					150	
ED/LED/220D	4	3	1.20Kg					150	

* Power shown in low Voltage operation to aid sizing of central systems.

OPTIONS

Products incorporating any of the following options are manufactured to order. Some options may not be available in all models.

- /2K7 2700K colour temperature
- /3K 3000K colour temperature
- /5K 5000K colour temperature
- /6K5 6500K colour temperature
- /DAE DALI emergency mode only
- /ED/WH White semi-recessing kit
- /M IP65 metal base
- /SAL1 BS5499 format self-adhesive legend kit
- /SAL1/7010 EN7010 format self-adhesive legend kit
- /ST Digital self-test
- /TS Push-to-test switch
- /VR Anti-tamper screws

DIMENSIONS

LUMINAIRE DIMENSIONS

Length 350mm x Width 108mm x Depth 80mm

CUT-OUT DIMENSIONS

Length 330mm x Width 90mm (when supplied with ED/WH semi-recessing kit)

VIEWING DISTANCE

18 Metres (when supplied with self-adhesive legend kit)

SPECIFICATION

GENERAL

Country of Origin: United Kingdom.
CE Mark Compliance: CE marked, REACH and RoHS compliant.
Manufactured to Standards: BS EN60598-2-1 (mains), BS EN60598-2-22 (emergency).
Manufacturing Quality Approval: ISO 9001:2015.

CONSTRUCTION

Body Construction: 850°C compliant polycarbonate.
Body Finish: White.
Protection Degree: IP65.
Insulation Class: Class 1.
Light Distribution Category: General.
Reflector Material: Sheet steel.
Reflector Type: Flat gear tray style.
Reflector Finish: White powder coated.
Diffuser Material: Self-extinguishing polycarbonate.
Diffuser Type: Clear.
Diffuser Finish: Patterned.
Cabling: 90°C single core 0.8mm to BS6500 Grade 5.
Supply Voltage: 230/240V AC 50/60Hz (replace 230V with 24V, 50V, 110V or 220V for slave versions).

LED CONTROL GEAR

Mains Luminaires:

CAT NO	V-OUT	I-OUT
ED/LED	3V	350mA
ED/LEDH	8V	350mA

- Designed and manufactured in accordance with BS EN61347-2-13, BS EN62384, BS EN55015, BS EN61000-3-2 and BS EN61000-3-3.

Emergency Luminaires:

CAT NO	V-OUT	I-OUT
ED/LED/M3	3V	300mA
ED/LEDH/M3H	3V	450mA
ED/LED/NM3H	3V	850mA
ED/LEDH/C3	8V/3V	350mA/300mA
ED/LEDH/C3H	8V/3V	350mA/850mA

- Constant current output emergency LED drivers.
- Input Voltage 230/240V AC 50/60Hz.
- Designed and manufactured in accordance with BS EN61347-2-7, BS EN61347-2-13, BS EN62384, BS EN55015, BS EN61000-3-2 and BS EN61000-3-3.
- Certified to BS EN61347-2-13, BS EN62384, BS EN55015, BS EN61000-3-2 and BS EN61000-3-3.
- Suitable for use with Ni-Cad battery technology.

Slave Luminaires:

- Low Voltage LED control gear designed for use with low Voltage central systems, constant power output suitable for LED loads of 3-80V DC.
- Designed and manufactured in accordance with BS EN61347-2-13, BS EN62384, BS EN55015, BS EN61000-3-2 and BS EN61000-3-3.

CAT NO	V-OUT	I-OUT
24V slave variants	3V	350mA
50V slave variants	3V	350mA
110V slave variants	3V	350mA
220V slave variants	3V	350mA

LEDs

LED Type: 2835 SMT mid power.
LED Colour Temperature: 4000K (2700K-6500K available to order).
CRI Minimum: 80.
SDCM: 3 (MacAdam rating).
LED Lifetime: TM21 L70 >54,000 hours.
LED Manufacturer(s): Seoul semiconductor / Plessey / CREE or equivalent.

Orbik has a policy of constant product improvement and therefore reserve the right to modify specifications without prior notice. All details and specifications shown within this data sheet are deemed correct at the time of print.



HEAD OFFICE & EXPORT SALES

Orbik Electronics Limited, Orbik House, Northgate Way, Aldridge, Walsall, West Midlands, WS9 8TX, United Kingdom
TEL: +44 (0) 1922 743515 FAX: +44 (0) 1922 743173 EMAIL: sales@orbik.co.uk Export Email: export@orbik.co.uk

UK WHOLESALE SALES

TEL: 01922 745024 FAX: 01922 745124 EMAIL: uksales@orbik.co.uk

www.orbik.co.uk