SMOKE & HEAT MULTI ALARM



PRODUCT FEATURES:

- Hush Nuisance Alarms
- Loose Neutral Monitoring
- Loud 85dB Alarm
- Tamper Proof Design
- Low Battery Warning
- 10-year Life Lithium Battery
- RF Module Compatible (HSSA/MOD/RF-PRO)
- The Ultimate Retrofit Solution



DESCRIPTION:

The HSSA/OH/10 & The HSSA/OH/10H are 230v powered Multi Sensor Alarms with 10year Rechargeable Lithium Batteries for Backup. The alarm contains a highly accurate sensor, thoroughly tested throughout the manufacturing process for fewer false activations and has been extensively calibrated for optimal fire safety.

Grade of Alarm:	D1
Detection Type:	Optical Smoke and Fixed Heat (60°C)
Power Source:	220-240v AC 50Hz
Backup Power Source:	Lithium Battery with 10-year Life
Approved/Manufactured To:	BS EN 14604:2005, BS 5446-2:2003
Designed For Installation To:	BS5839-6:2019
Alarm Sound Level:	85db at 3m
Ambient Operating Temp:	0°C to 40°C
Ambient Operating Humidity:	10% to 90%
Power Consumption (In Alarm):	≤40mA
Power Consumption (Standby):	≤10µA
Nin/Max Cable CSA:	0.75mm ² to 1.5mm ²
ED Indicator Function:	Green = Mains Power, Red = Battery/Fault Status
/arranty:	5 years
Max Interconnected Units:	20
Max Hardwire Interconnect Distance:	150m
Max RF Connected Units:	20
Max RF Distance:	Open Area 80m, Enclosed Area 30m
Backup Battery Life (No Mains):	30 days
itorage Temperature:	-10 to 50°C
Storage Humidity:	0 to 90% (non-condensing)















SMOKE & HEAT MULTI ALARM



INSTALLATION LOCATIONS:















Loft Extensions

PRODUCT CONSTRUCTION:

Plastic Housing Material:

Fire Retardant ABS


Weight (Unboxed):


260g (Head - 175g)

Cable Entry:

Rear Entry and Side (mini-trunking) Knockout

LINE DRAWINGS:









HEAT KM 792789 BS 5446-2:2003 CO

KM 792788 BS EN 14604:2005



















