# Ei630iRF



### RadioLINK+ Heat Alarm



- Heat sensor responds to heat build-up from large flaming fires (triggers at 58°C)
- AudioLINK+ data extraction technology
- 10 year Lithium battery powered
- RadioLINK+ Wireless interconnection
- Kitemarked to BS 5446-2:2003
- 5 year guarantee







Garage



#### Description

The Ei630iRF RadioLINK+ Heat Alarm is powered by a 10 year life sealed in Lithium cell. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

#### **Technical**

Sensor Type Heat (Al) RF Frequency (MHz) 868.499

Red - Power Up, Alarm, Silence

**RF Range (m)** >100 in free air **Indicators** Mode, Fault / Blue - RF

transmission

Battery Type Lithium primary Technologies AudioLINK+ / RadioLINK+

Dimensions & Weights

 Depth (mm)
 64
 Height (mm)
 120

 Width (mm)
 120
 Product weight (kg)
 0.206

Packaged weight (kg) 0.276

## Approvals & Warranty

**Certification/Approvals**BS 5446-2:2003 / EN 300 220-1 / EN 301 489-1

Warranty

5 year warranty

**EAN Number** 5099383010275

**Environmental** 

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

