8 WATT DOUBLE SIDED EXIT SIGN





The EDS light is a general purpose, double-sided interior ceiling mounted sign for use on intersections.

- White, stove-enamelled, zintec-coated sheet steel base.
- Self-extinguishing polycarbonate legend panel.
- Designed for use on escape routes.
- Passes the 850°C hot-wire test, defined by ICEL..
- Complying with the requirements of EN60598-2-22.
- Suitable for incorporation into an emergency lighting system complying with BS5266-1:2011.
- Full range of finishes are available including any British Standard or RAL colour.
- Switchable, Maintained and Non-Maintained versions available.

Specification

- IP20 (Interior Use)
- Escape Route Sign
- Choice of Legend
- Ceiling Mounted
- Colour Options
- Self Contained
- 24, 50, 110V ACDC options available



Options

Options	
/BR	Brass finish
/CR	Chrome finish.
/LR	Arrow left / Arrow right
/UD	Arrow up / Arrow down
/ST	Self test
/TS	Test switch
/DALI	DALI

Note: All exit signs are arrow down as standard please specify other direction if required

Viewing Distance


Viewing Distances

34 Metres

Suitable Applications

- Suitable for interiour escape routes and intersections.
- Suitable for incorporation into an emergency lighting system complying with B\$5266-1:2011.

Dimensions





Technical Specification

natai

	Model	Lamp Type	Power Con	Battery	Duration	Weight
EDS8NM	Non Maintained	8W T5	8 W	2.4V 4Ah	3 Hours	2.18 Kg
EDS8M	Maintained	8W T5	20 W	2.4V 4Ah	3 Hours	2.35 Kg
EDS8/SL/*	ACDC Slave. * suffix voltage	ACDC Slave. * suffix voltage required with 24, 50, 110				

36335 – sales@ringtail.co.uk

EDS8/230/HF Mains only / Static inverter

Installation Notes

.

Cable knockout provided on the top of unit.

Materials / Finish

- White stove-enamelled zintec-coated sheet steel base.
- Alternative finishes available: Any British Standard or RAL colour

Catalogue Numbers

EDS8NM	Non Maintained			
EDS8M	Maintained			
EDS8/SL/*	ACDC Slave. * suffix voltage required with 24, 50, 110			
EDS8/230/HF	Mains only / Static inverter			

