



FirePower



FOAM EXTINGUISHERS - CARTRIDGE OPERATED

- Kitemarked to BS EN3
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base
- Complete with wall bracket
- Branchpipe model is also suitable for alcohol risks
- 6ltr & 9ltr foam spray extinguishers have
- Passed the 35kv conductivity discharge test

Type	AFFF Spray	AFFF Spray	FFFP-AR Branchpipe Spray
Capacity (kg)	6	9	9
Fire rating	13A 144B	21A 183B	21A 183B
Height (mm)	560	600	600
Cylinder diameter (mm)	160	189	189
Overall width (mm)	310	330	380
Filled weight (kg)	10.67	15	15.1
Range of throw (m)	>4	>4	>4
Duration of discharge (secs)	30	40	35
Working pressure (at 20°C)	14 bar	10 bar	15 bar
Temperature range (°C)	0 to 60	0 to 60	0 to 60
BS EN3 approved	✓	✓	✓
MED approved		✓	✓
Part number	9214/00	9215/00	9216/00
Model number	FPF6C	FPF9C	FPF9BC



Tel: 0161 654 2222 | Freefax: 0800 281 035

Website: www.thomas-glover.co.uk | Email: tgsales@tgproducts.co.uk



TG Products Ltd, Parkfield House, Manchester Old Road, Middleton, Manchester, M24 4DY