



FirePower



FOAM EXTINGUISHERS - CARTRIDGE OPERATED

- Kitemarked to BS EN3
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base
- Complete with wall bracket
- Branchpipe model is also suitable for alcohol risks
- 6ltr & 9ltr foam spray extinguishers have
- Passed the 35kv conductivity discharge test

| Type | AFFF Spray | AFFF Spray | FFFP-AR Branchpipe Spray |
|------------------------------|------------|------------|--------------------------|
| Capacity (kg) | 6 | 9 | 9 |
| Fire rating | 13A 144B | 21A 183B | 21A 183B |
| Height (mm) | 560 | 600 | 600 |
| Cylinder diameter (mm) | 160 | 189 | 189 |
| Overall width (mm) | 310 | 330 | 380 |
| Filled weight (kg) | 10.67 | 15 | 15.1 |
| Range of throw (m) | >4 | >4 | >4 |
| Duration of discharge (secs) | 30 | 40 | 35 |
| Working pressure (at 20°C) | 14 bar | 10 bar | 15 bar |
| Temperature range (°C) | 0 to 60 | 0 to 60 | 0 to 60 |
| BS EN3 approved | ✓ | ✓ | ✓ |
| MED approved | | ✓ | ✓ |
| Part number | 9214/00 | 9215/00 | 9216/00 |
| Model number | FPF6C | FPF9C | FPF9BC |



Tel: 0161 654 2222 | Freefax: 0800 281 035

Website: www.thomas-glover.co.uk | Email: tgsales@tgproducts.co.uk



TG Products Ltd, Parkfield House, Manchester Old Road, Middleton, Manchester, M24 4DY