

8. False Alarms

In order to carry out its function properly, the unit is set to be very sensitive. Therefore the unit may react to other gases e.g. Aerosols (propellants in hairsprays, disinfectants etc.) and strong tobacco smoke.

9. Specifications

230 V AC: approx. 4 Watt
Temperature Range: -15°C / +40°C

10. Gas detection Levels

Sensitivity Setting Values

Propane	0.5%
Butane	0.4%
Methane (City Gas / Natural Gas)	0.8%

11. Safety advice

- o The function test must be repeated from time to time, particularly in case of frequent and long-term rest periods. Thereby, the operating of the siren and the sensor are checked.
- o Strictly observe also the installation height in accordance to the kind of gas!
- o Not to be used in the open!

12. Care of Unit

The housing of the unit can be cleaned using a duster or chamois.

From time to time gently vacuum the sensor openings (the round openings on top), depending on the conditions of the alarm.

The unit should never be cleaned using water - water can damage the electronics.

Do not open the unit - this will result in loss of guarantee and can damage the unit.

13. Waste disposal

Electrical appliances must not be disposed of with the normal household waste. According to the applicable legal prescription, used up electrical appliances must be put to an environment-friendly recycling. Transport the device which has had its day to a waste disposal plant of your town or community.

14. Guarantee

We furnish a guarantee of two years on this appliance, starting from the purchase date.

The warranty shall apply exclusively to defects in material and workmanship. Further or other claims, especially those for indemnification for personal injury and damage to property occurring outside the device, shall be excluded. We shall not be obliged to assume a repair or the replacement of parts whose faults are due to misuse, damage, or alteration after the purchase date. The liability obligation ensuing for us from the sale of the gasalarm shall not exceed the costs for the replacement of the product in any case. We shall not be held liable in any case for consequential losses resulting from the defect of the product. The guarantee shall be valid in connection with the purchase receipt, which has to be sent in together with the appliance. In case of interventions in the appliance, the warranty claim shall lapse.

The product is exclusively intended for private and not industrial use.

Manufacturer:

Automatische Mess- und
Steuerungstechnik GmbH

Enge Gasse 1, D-91275 Auerbach/Opf., Germany

Phone.: +49(0)9643 / 9205-0

Fax: +49(0)9643 / 9205-90

E-mail: info@ams-messtechnik.de