

8 WATT SURFACE MOUNTED EXIT SIGN


The TPX/EX Light is an attractive, surface mounted, versatile emergency edge illuminated escape and direction sign luminaire for interior use.

This combined unit has a legend that is illuminated through the diffuser and acts as a down lighter to provide extra lighting. Comprising a moulded, polycarbonate base and fitted with a clear flame retardant diffuser, the TPX/EX Light is designed for use on escape routes. The diffuser is screw fixed to the base to provide a seal to IP20. The gear tray is easily removable to allow first fix of the base. Cable knockouts are provided in the ends and a BESA entry in the base. The TPX/EX Light complies with the requirements of EN60598-2-22 and is suitable for incorporation into an emergency lighting system complying with BS5266-1:2011. White with a clear fresnel diffuser as standard. Switchable, Maintained and Non-Maintained versions available.



Viewing Distances 27 Metres

	Mode	Lamp Type	Power Con	Battery	Duration	Weight
TPX8NM/EX	Non Maintained	8W T5	8 W	2.4V 4Ah	3 Hours	1.93 Kg
TPX8M/EX	Maintained	8W T5	20 W	2.4V 4Ah	3 Hours	2.10 Kg
TPX8/EX/SL/*	ACDC Slave. * suffix voltage required with 24, 50, 110					
TPX8/EX/230/HF	Mains only / Static inverter					



Options

/LR	Arrow left / right
/DS	Double sided legend
/ST	Self test
/TS	Test switch
/DALI	DALI

Note: All exit signs are arrow down as standard please specify other direction if required

- IP20 (Interior Use)
- Escape Route Sign
- Downlight Facility
- Choice of Legend
- Ceiling Mounted
- Self - Contained
- For use on intersections

