

# RECESSED LED EXIT SIGN

This X-MPRL is a decorative, illuminated escape route and direction sign light.

Using high illumination white LED's, in a small compact shell, with self test/Dali facility, it is virtually maintenance free. Designed to be recess mounted in ceilings allowing escape route lighting, it provides a low profile emergency lighting option. Comprising of a stove enamelled sheet steel base fitted with a white bezel, suitable for use on escape routes. The bezel is attached by captive screws and provides a seal to IP20. The gear tray is hinged for ease of installation and is easily removable to allow first fix of the base. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2005. The X-MPRL Light is switchable maintained and available in white or chrome finishes.



## Viewing Distances

X-MPRL	17 Metres
--------	-----------

Model	Mode	Lamp	Battery	Power Con	Duration	Weight	Output (lumens)
X-MPRL3M	M/NM (Self test)	6 LED's	3.6V 3Ah NiMh	7 W	3 Hours	1.65 Kg	150
X-MPRL3M/DALI	M/NM (Dali)	8 LED's	3.6V 2Ah NiMh	4 W	3 Hours	1.95 Kg	80

## Options

/CR	Chrome finish
/BR	Brass finish
/L	Arrow Left
/R	Arrow Right
/DALI	DALI

Note: All exit signs are arrow down as standard, specify other direction if required. Please ask for ISO 7010:2011 Legends.

- Self test/DALI
- Hinged gear tray
- Recess mount
- White high output LED's
- IP20
- Chrome and brass finishes available

