

The SR Light is a slimline circular anti-ligature, luminaire suitable for interior environments. Comprising of a spun aluminium housing with a polycarbonate opal diffuser, suitable for use on escape routes (850 degrees C Hot-Wire test, defined by ICEL). The diffuser is held in place by a security screw fixed rim, which fits flush to the ceiling. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2005. The SR Light offers an effective solution to combine emergency lighting and mains lighting, or where higher light levels are required, available in white with special finishes, such as brass, chrome and black to order.

TYPICAL APPLICATIONS

- Corridors**
- Stairwells**
- Office complexes**
- Night Clubs**
- Healthcare institutions**



- IP40
- Tamper proof screws
- U.V. stabilised opal diffuser
- High Light Output
- 28w 2d Lamp
- Colour Options Available
- Self-Contained
- Centrally Supplied
- Powder coated finish



	Mode	Lamp Type	Power Con	Battery	Duration	Weight	Output	Dimensions
SR28M	Maintained	28W 2D	39 VA	3.6V 4Ah	3 Hours	2.7 Kg	205 Lumens	475 Dia x 140 Deep
SR28/SL/*	Mains or Slave	28W 2D	30 VA			2.5 – 3.2 Kg		
SR28S	Sustained (Combined)	28W 2D & 7W PL	39 VA	3.6V 4Ah	3 Hours	2.9 Kg	80 Lumens	

Please suffix voltage required i.e. 24, 50, 110, 230 /ST - Self Test

Open area	Model	Height (m)	1 Lux floor luminosity		0.5 Lux floor luminosity	
			Diagram	Distance (m)	Diagram	Distance (m)
		2.5		2.86		3.72
		4		6.99		4.12
		6		5.80		3.75
	SR28M					
						8.81
						10.55
						10.58