

The EDS light is an general purpose, double sided emergency escape route sign suitable for internal environments and with the added advantage of being able to take a full size escape route legend. Comprising of a white stove enamelled, zintec coated sheet steel base fitted with a self extinguishing legend panel, suitable for use on escape routes (850 degree C Hot-wire test, defined by ICEL). The EDS light has a cable knockout, which is provided in the top. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2005. The EDS light can be fitted with legends complying with the Health and Safety signs directive of 1996, while for extensions a full range of BS5499 legends remain available. With flexibility in mind a full range of alternative finishes are available including any British Standard or RAL colour.



- IP20 Interior Use
- Escape Route Sign
- Downlight Facility
- Choice of Legend
- Ceiling or wall Mounted
- Colour Options Available
- Central Battery Versions
- Self-Contained
- Centrally Supplied

	Mode	Lamp Type	Power Con	Battery	Duration	Weight	Emerg Output	Dimensions
EDS8NM	Non Maintained	8W T5	8 VA	2.4V 4Ah	3 Hours	1.4 Kg	100 Lumens	380 x 190 x 115
EDS8M	Maintained	8W T5	20 VA	2.4V 4Ah	3 Hours	1.75 Kg	100 Lumens	
EDS8/SL/*	Mains or Slave	8W T5	7 - 20 VA			1.2 - 1.5 Kg	270 Lumens	

\* Please suffix voltage required i.e. 24, 50, 110, 230

Suffix part number with

/L	-	Left Arrow
/R	-	Right Arrow
/BR	-	Brass finish
/CR	-	Chrome finish
/ST	-	Self Test

