



---

## CERTIFICATE OF APPROVAL

### No CF 389

---

This is to certify that, in accordance with  
TS00 General Requirements for Certification of Fire Protection Products  
The undermentioned products of

**EXIDOR LIMITED**  
**ASSA Abloy Opening Solutions UK & Ireland,**  
**School Street,**  
**Willenhall,**  
**WV13 3PW**  
**Tel. 07557 231463**

Have been assessed against the requirements of the Technical Schedule(s)  
denoted below and are approved for use subject to the conditions  
appended hereto:

---

#### CERTIFIED PRODUCT

**Exidor 200/300 Series Panic Exit  
Devices, Exidor 400 Series Touch  
Bar Devices & Exidor 500 Series  
(Slimline) Panic Exit Devices**

#### TECHNICAL SCHEDULE

**TS26 The Contribution of Panic  
Exit Devices to the Fire  
Resistance of Door Assemblies**

**Signed and sealed for and on behalf of Warringtonfire Testing and Certification Limited**

**Paul Duggan**  
**Certification Manager**



Issued: 19<sup>th</sup> November 2004  
Revised: 23<sup>rd</sup> August 2022  
Valid to: 7<sup>th</sup> March 2026

Page 1 of 12





---

## CERTIFICATE No CF389

### EXIDOR LIMITED

---

#### **Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

1. This certification is provided to the client for their own purposes and we cannot opine on whether it will be accepted by Building Control authorities or any other third parties for any purpose.
2. This approval relates to the Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices identified in Annex A only.
3. This approval relates to the use of the family of exit devices with the following door assemblies:

**Previously proven unlatched, intumescent sealed door assemblies consisting of timber faced and edged leaves with timber, cellulosic or mineral cores, in timber having a fire resistance up to 120 minutes (Code ITT) \*.**

**Previously proven unlatched, intumescent sealed door assemblies consisting of timber faced and edged leaves with timber, cellulosic or mineral cores, in steel frames having a fire resistance up to 120 minutes (Code ITM) \*<sup>✓</sup>.**

**Previously proven unlatched, 20 minute to 120 minute assemblies containing intumescent seals and consisting of timber faced and edged leaves with timber, cellulosic or mineral cores, hung in proprietary composite frames, of which the principal material is other than timber or metal but which may include any other materials (Code ITC)\*<sup>✓</sup>.**

**Previously proven unlatched door assemblies consisting of uninsulated or insulated predominantly steel leaves, hung in steel frames with or without intumescent seals having a fire resistance up to 240 minutes (Code IMM/MM) <sup>✓</sup>.**

\* Excludes the 305SD, 420 & 421 panic mortice actuators with cylinder nightlatch

<sup>✓</sup> Excludes Exidor 400 Touchbar Series with Electronic Latch Retraction (ELR).



---

## CERTIFICATE No CF389

### EXIDOR LIMITED

---

#### **Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

4. The exit devices are approved on the basis of:
- i) Initial type testing to EN 1125 for mechanical properties
  - ii) Initial type testing to EN 1634-1 for the fire resistance performance of doorsets
  - iii) An appraisal against TS26
  - iv) Certification of quality management system to ISO 9001: 2008.
  - v) Inspection and surveillance of factory production control
  - vi) On-going audit testing in accordance with EN 1125:2008
5. This approval is applicable only to the specified exit devices and relevant accessories when used with door assemblies of proven fire resistance (as defined in BS 476: Part 22: 1987 and EN 1634-1) which have previously been successfully tested unlatched but fitted with a CERTIFIRE approved door closer. Failure to install the device and accessories in the appropriate manner will invalidate this certificate of approval.
6. It is a requirement of this report that the doorsets to which the panic hardware is fitted shall have been previously tested unlatched in the configuration required. The purpose of the appraisal is only to consider the influence of fitting the proposed hardware items to a doorset, and not its ability to provide an essential latching action.
7. Where the Exidor 400 Touchbar Series with Electronic Latch Retraction (ELR) are fitted to ITT doorsets, the doorset shall be fully insulated for the required classification period as defined by BS476; Part 22 or EN1634-1.
8. The spindle hole through the door shall be a maximum of 15 mm diameter unless the doorset has test evidence that proves spindle holes of a greater size than this.
9. Recessing for cylinder mortice nightlatch shall result in a tight fit without voids.
10. Cylinders shall only be fitted to MM/IMM doors which have previously been shown capable of accommodating the installation of cylinder locks without detriment to the doorset's performance.
11. The mortice locks may incorporate Euro profile cylinders as follows:
- i) Single cylinder
  - ii) Double cylinder
  - iii) Cylinder and thumbturn
  - iv) Steel cylinders only

*Note: The hole in the door face shall follow the shape of the cylinders and be as tight as possible; furthermore the single cylinders door preparation will penetrate through only half the thickness of the door leaf)*



---

## CERTIFICATE No CF389

### EXIDOR LIMITED

---

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

12. The hardware shall only be fitted to ITC doorsets which have previously been shown capable of accommodating the installation of surface mounted panic and escape hardware, without detriment to the doorset's performance.
13. The approval relates to on-going production. The product and/or its immediate packaging is identified with the manufacturer's name, the product name or number, the CERTIFIRE name or name and mark, together with the CERTIFIRE certificate number and application where appropriate.



## CERTIFICATE No CF389 EXIDOR LIMITED

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

7. The following table shows acceptable doorset types and fire resistance periods for all products except the Exidor 400 Touchbar Series with Electronic Latch Retraction (ELR):

Class	Approved Door Type				
	IMM	MM	ITT	ITM	ITC
FD20	✓	✓	✓*	✓*	✓*
FD30	✓	✓	✓*	✓*	✓*
FD60	✓	✓	✓*	✓*	✓*
FD90	✓	✓	✓*	✓*	✓*
FD120	✓	✓	✓*	✓*	✓*
FD240	✓	✓	x	✓*	✓*
E 20	✓	✓	✓*	✓*	✓*
EI 20	✓	✓	✓*	✓*	✓*
E 30	✓	✓	✓*	✓*	✓*
EI 30	✓	✓	✓*	✓*	✓*
E 60	✓	✓	✓*	✓*	✓*
EI 60	✓	✓	✓*	✓*	✓*
E 90	✓	✓	✓*	✓*	✓*
EI 90	✓	✓	✓*	✓*	✓*
E 120	✓	✓	✓*	✓*	✓*
EI 120	✓	✓	✓*	✓*	✓*
E 240	✓	✓	x	x	x
EI 240	✓	✓	x	x	x

**Key:**

- ✓ - approved
- x - Not approved
- ✓\* - Excludes the 305SD, 420 & 421 panic mortice actuators with cylinder mortice nightlatch.



## CERTIFICATE No CF389 EXIDOR LIMITED

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

7. The following table shows acceptable doorset types and fire resistance periods for the Exidor 400 Touchbar Series with Electronic Latch Retraction (ELR) only:

Class	Approved Door Type				
	IMM	MM	ITT	ITM	ITC
FD20	x	x	✓*✓	x	x
FD30	x	x	✓*✓	x	x
FD60	x	x	✓*✓	x	x
FD90	x	x	✓*✓	x	x
FD120	x	x	✓*✓	x	x
FD240	x	x	x	x	x
E 20	x	x	x	x	x
EI 20	x	x	✓*	x	x
E 30	x	x	x	x	x
EI 30	x	x	✓*	x	x
E 60	x	x	x	x	x
EI 60	x	x	✓*	x	x
E 90	x	x	x	x	x
EI 90	x	x	✓*	x	x
E 120	x	x	x	x	x
EI 120	x	x	✓*	x	x
E 240	x	x	x	x	x
EI 240	x	x	x	x	x

**Key:**

- ✓ - approved
- x - Not approved
- ✓\* - Excludes the 305SD, 420 & 421 panic mortice actuators with cylinder mortice nightlatch.
- ✓✓ - The doorset shall be fully insulated for the required classification period as defined by BS476; Part 22



---

## CERTIFICATE No CF389 EXIDOR LIMITED

---

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

8. Doors are classified as the following types:

**Code ITT - 20 minute to 120 minute doorsets containing intumescent seals and consisting of timber faced and edged leaves with timber, cellulosic or mineral cores, hung in timber-based frames.**

**Code ITM - 20 minute to 120 minute doorsets containing intumescent seals and consisting of timber faced and edged leaves with timber, cellulosic or mineral cores, hung in metal frames.**

**Code ITC - 20 minute to 120 minute doorsets containing intumescent seals and consisting of timber faced and edged leaves with timber, cellulosic or mineral cores, hung in proprietary composite frames, of which the principal material is other than timber or metal but which may include any other materials.**

**Code MM - 20 to 240 minute doorsets consisting of uninsulated or insulated predominantly steel leaves, hung in steel frames without intumescent seals.**

**Code IMM - 20 to 240 minute doorsets consisting of uninsulated or insulated predominantly steel leaves, hung in steel frames with intumescent seals.**

**Scope of Approval:**

- The panic hardware may not be fitted to timber doorsets without perimeter intumescent fire seals within the frame rebate or edge of the door leaf.
- The following associated external access devices may be installed onto 30 or 60 minute ITT timber doorsets, and IMM and MM uninsulated and insulated steel based door leaves for up to 240 minute performances:

<b>200/300 Series</b>	<b>400 Series</b>	<b>500 Series</b>
298 (knob)	409 (knob)	500/LEA
302EA (knob)	410EA (lever)	500/LEC
302EC (knob)	410EC (lever)	500/KEA
302OA (knob)	410OA (lever)	500/KEC
302OC (knob)	410OC (lever)	
322EA (lever)	411EA (knob)	
322EC (lever)	411EC (knob)	
	411OA (knob)	
	411OC (knob)	



**CERTIFICATE No CF389  
EXIDOR LIMITED**

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

**Scope of Approval Cont'd:**

- The following 'Universal' external access devices may be installed onto 30 or 60 minute ITT timber doorsets, and IMM and MM uninsulated and insulated steel based door leaves for up to 240 minute performances:

<b>200/300 SERIES</b>	
325EC Silver	Lever OAD Euro W/Lock 200 Series OAD
325EA Silver	Lever OAD Euro W/Out Lock 200 Series OAD
326EC Silver	Knob Operated OAD Euro W/Lock 200 Series OAD
326EA Silver	Knob Operated OAD Euro Nolock 200 Series OAD
<b>400 SERIES</b>	
425EC Silver	Lever OAD Euro W/Lock 400 Series OAD
425EA Silver	Lever OAD Euro W/Out Lock 400 Series OAD
426EC Silver	Knob Operated OAD Euro W/Lock 400 Series OAD
426EA Silver	Knob Operated OAD Euro Nolock 400 Series OAD
<b>500 SERIES</b>	
525EC Silver	Lever OAD Euro W/Lock 500 Series OAD
525EA Silver	Lever OAD Euro W/Out Lock 500 Series OAD
526EC Silver	Knob Operated OAD Euro W/Lock 500 Series OAD
526EA Silver	Knob Operated OAD Euro Nolock 500 Series OAD

- The door leaves for ITT timber based doorsets for 30 or 60 minute performances shall have a minimum leaf thickness of 44 mm and 54 mm, for 30 and 60 minute doorsets respectively.
- The door leaves for IMM and MM steel based doorsets for up to 240 minute performances shall have a minimum leaf thickness 45 mm.

**Classification codes**

The approval provides the following classifications:

**Exidor 200, 300 & 500 Panic Exit Device Series:**

3	7	6	B	1	3	2	2	A	A
---	---	---	---	---	---	---	---	---	---

**Exidor 400 Series Touch Bar Devices**

3	7	6	B	1	3	2	2	B	A
---	---	---	---	---	---	---	---	---	---



---

**CERTIFICATE No CF389**  
**EXIDOR LIMITED**

---

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices  
& Exidor 500 Series (Slimline) Panic Exit Devices.**

**Further Information**

Further information regarding the details contained in this data sheet may be obtained from Exidor Ltd (Tel: 01543 578661).

Further information regarding CERTIFIRE certification and other approved products can be obtained from CERTIFIRE (Tel: 01925 646777).



## CERTIFICATE No CF389 EXIDOR LIMITED

Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices  
& Exidor 500 Series (Slimline) Panic Exit Devices.

### Annex A

Reference	Description
<b>Exidor 200/300 Pushbar Series</b>	
<b>284</b>	Double Door Set (two single panic bolts)
<b>284SD</b>	Double Door Set (two single panic bolts)– Steel door fixing
<b>284A</b>	Double Door Set (two single panic bolts)– Adjustable shoots
<b>284A/SD</b>	Double Door Set (two single panic bolts)– Steel door fixing/ Adjustable shoots
<b>285</b>	Double Door Set (panic latch & panic bolt)
<b>285SD</b>	Double Door Set (panic latch & panic bolt)– Steel door fixing
<b>285A</b>	Double Door Set (panic latch & panic bolt)– Adjustable shoots
<b>285A/SD</b>	Double Door Set (panic latch & panic bolt)– Steel door fixing/ Adjustable shoots
<b>294</b>	Single Panic Bolt
<b>294SD</b>	Single Panic Bolt – Steel door fixing
<b>294A</b>	Single Panic Bolt – Adjustable shoots
<b>294A/SD</b>	Single Panic Bolt – Steel door fixing/ Adjustable shoots
<b>296</b>	Reversible Panic Latch
<b>296SD</b>	Reversible Panic Latch – Steel door fixing
<b>305SD</b>	Panic Mortice Actuator with Cylinder Mortice Night Latch – Steel door fixing
<b>308</b>	Double Door Set (two single panic bolts)
<b>308SD</b>	Double Door Set (two single panic bolts)– Steel door fixing
<b>309</b>	Double Door Set (panic bolt with horizontal Pullman latches + second panic bolt with vertical Pullman latches)
<b>309SD</b>	Double Door Set (panic bolt with horizontal Pullman latches + second panic bolt with vertical Pullman latches) – Steel door fixing
<b>311</b>	Single Panic Bolt with Vertical Pullman Latches
<b>311SD</b>	Single Panic Bolt with Vertical Pullman Latches – Steel door fixing
<b>316</b>	Double Door Set (two single panic bolts with vertical Pullman latches)
<b>316SD</b>	Double Door Set (two single panic bolts with vertical Pullman latches)– Steel door fixing
<b>317</b>	Double Door Set (panic latch + panic bolt with vertical Pullman latches)
<b>317SD</b>	Double Door Set (panic latch + panic bolt with vertical Pullman latches) – Steel door fixing
<b>Exidor 400 Touchbar Series</b>	
<b>401</b>	Touch Bar Panic Latch
<b>402</b>	Touch Bar Panic Bolt With Vertical Latches
<b>403</b>	Touch Bar Panic Bolt With Vertical Latches
<b>404</b>	Touch Bar Three Point Panic Bolt With Vertical Latches
<b>405</b>	Touch Bar Three Point Panic Bolt With Vertical Latches
<b>416</b>	Touch Bar Panic Bolt With Horizontal Latches
<b>417</b>	Touch Bar Panic Bolt With Horizontal Latches
<b>418</b>	Touch Bar Three Point Panic Bolt With Horizontal Latches
<b>419</b>	Touch Bar Three Point Panic Bolt With Horizontal Latches
<b>420</b>	Touch Bar Mortice Actuator With Cylinder Night Latch
<b>421</b>	Touch Bar Mortice Actuator With Cylinder Night Latch

Page 10 of 12  
Signed  
E/487

Issued: 19<sup>th</sup> November 2004  
Revised: 23<sup>rd</sup> August 2022  
Valid to: 7<sup>th</sup> March 2026



## CERTIFICATE No CF389 EXIDOR LIMITED

Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices  
& Exidor 500 Series (Slimline) Panic Exit Devices.

### Annex A – Cont'd

<b>Exidor 400 Touchbar Series with Electronic Latch Retraction (ELR)</b>	
<b>TB450</b>	Touch-bar 1PT Latch – With Dogging – For Doors Up To 900mm Wide – With ELR
<b>TB450AL</b>	Touch-bar 1PT Latch – With Dogging – For Doors Up To 900mm Wide – With Alarm & ELR
<b>TB450MS</b>	Touch-bar 1PT Latch – With Dogging – For Doors Up To 900mm Wide – With Microswitch & ELR
<b>TB451</b>	Touch-bar 1PT Latch – With Dogging – For Doors Up To 1200mm Wide – With ELR
<b>TB451AL</b>	Touch-bar 1PT Latch – With Dogging – For Doors Up To 1200mm Wide – With Alarm & ELR
<b>TB451MS</b>	Touch-bar 1PT Latch – With Dogging – For Doors Up To 1200mm Wide – With Microswitch & ELR
<b>TB452</b>	Touch-bar 2PT With Vertical Pullmans – With Dogging – For Doors Up To 900mm Wide – With ELR
<b>TB452AL</b>	Touch-bar 2PT With Vertical Pullmans – With Dogging – For Doors Up To 900mm Wide – With Alarm & ELR
<b>TB452MS</b>	Touch-bar 2PT With Vertical Pullmans – With Dogging – For Doors Up To 900mm Wide – With Microswitch & ELR
<b>TB453</b>	Touch-bar 2PT With Vertical Pullmans – With Dogging – For Doors Up To 1200mm Wide – With ELR
<b>TB453AL</b>	Touch-bar 2PT With Vertical Pullmans – With Dogging – For Doors Up To 1200mm Wide – With Alarm & ELR
<b>TB453MS</b>	Touch-bar 2PT With Vertical Pullmans – With Dogging – For Doors Up To 1200mm Wide – With Microswitch & ELR
<b>TB454</b>	Touch-bar 3PT With Vertical Pullmans & Centre Latch – With Dogging – For Doors Up To 900mm Wide – With ELR
<b>TB454AL</b>	Touch-bar 3PT With Vertical Pullmans & Centre Latch – With Dogging – For Doors Up To 900mm Wide – With Alarm & ELR
<b>TB454MS</b>	Touch-bar 3PT With Vertical Pullmans & Centre Latch – With Dogging – For Doors Up To 900mm Wide – With Microswitch & ELR
<b>TB455</b>	Touch-bar 3PT With Vertical Pullmans & Centre Latch – With Dogging – For Doors Up To 1200mm Wide – With ELR
<b>TB455AL</b>	Touch-bar 3PT With Vertical Pullmans & Centre Latch – With Dogging – For Doors Up To 1200mm Wide – With Alarm & ELR
<b>TB455MS</b>	Touch-bar 3PT With Vertical Pullmans & Centre Latch – With Dogging – For Doors Up To 1200mm Wide – With Microswitch & ELR
<b>TB466</b>	Touch-bar 2PT With Horizontal Pullmans – With Dogging – For Doors Up To 900mm Wide – With ELR
<b>TB466AL</b>	Touch-bar 2PT With Horizontal Pullmans – With Dogging – For Doors Up To 900mm Wide – With Alarm & ELR
<b>TB466MS</b>	Touch-bar 2PT With Horizontal Pullmans – With Dogging – For Doors Up To 900mm Wide – With Microswitch & ELR



---

## CERTIFICATE No CF389

### EXIDOR LIMITED

---

**Exidor 200/300 Series Panic Exit Devices, Exidor 400 Series Touch Bar Devices & Exidor 500 Series (Slimline) Panic Exit Devices.**

**Annex A – Cont'd**

<b><i>Exidor 400 Touchbar Series with Electronic Latch Retraction (ELR)</i></b>	
<b><i>TB467</i></b>	Touch-bar 2PT With Horizontal Pullmans – With Dogging – For Doors Up To 1200mm Wide – With ELR
<b><i>TB467AL</i></b>	Touch-bar 2PT With Horizontal Pullmans – With Dogging – For Doors Up To 1200mm Wide – With Alarm & ELR
<b><i>TB467MS</i></b>	Touch-bar 2PT With Horizontal Pullmans – With Dogging – For Doors Up To 1200mm Wide – With Microswitch & ELR
<b><i>TB468</i></b>	Touch-bar 3PT With Horizontal Pullmans & Centre Latch – With Dogging – For Doors Up To 900mm Wide – With ELR
<b><i>TB468AL</i></b>	Touch-bar 3PT With Horizontal Pullmans & Centre Latch – With Dogging – For Doors Up To 900mm Wide – With Alarm & ELR
<b><i>TB468MS</i></b>	Touch-bar 3PT With Horizontal Pullmans & Centre Latch – With Dogging – For Doors Up To 900mm Wide – With Microswitch & ELR
<b><i>TB469</i></b>	Touch-bar 3PT With Horizontal Pullmans & Centre Latch – With Dogging – For Doors Up To 1200mm Wide – With ELR
<b><i>TB469AL</i></b>	Touch-bar 3PT With Horizontal Pullmans & Centre Latch – With Dogging – For Doors Up To 1200mm Wide – With Alarm & ELR
<b><i>TB469MS</i></b>	Touch-bar 3PT With Horizontal Pullmans & Centre Latch – With Dogging – For Doors Up To 1200mm Wide – With Microswitch & ELR

<b><i>Exidor 500 Slimline Series</i></b>	
<b><i>501-B</i></b>	Push Bar Panic Latch
<b><i>502A-B</i></b>	Push Bar Panic Bolt
<b><i>503A-B</i></b>	Push Bar Three Point Panic Bolt
<b><i>512-B</i></b>	Push Bar Panic Bolt With Vertical Latches
<b><i>513-B</i></b>	Push Bar Three Point Panic Bolt With Vertical Latches
<b><i>522-B</i></b>	Push Bar Panic Bolt With Horizontal Latches
<b><i>523-B</i></b>	Push Bar Three Point Panic Bolt With Horizontal Latches