PowerX

Powder extinguishers

Stored pressure

- Kitemarked to BS EN3
- High quality product
- Supplied with plastic skirt to prevent damage to extinguisher base
- Complete with wall bracket
- Nickel plated brass valve assembly
- Coated steel levers
- Polyester external coating
- Easy gauge testing (with needle test)
- Approved to the Pressure Equipment Directive

- Inclusive of pressure release valve
- 5 year warranty
- **Supplied with Bracket & Strap



Туре	ABC Powder SP					
Capacity (Itr)	1	2	3	4	6	9
Fire Rating	5A 34BC	13A 70BC	13A 89B	21A 89BC	27A 144BC	34A 183BC
Height (mm)	330mm	390mm	430mm	495mm	545mm	590mm
Cylinder Diameter (mm)	85mm	110mm	125mm	140mm	150mm	184mm
Overall Width (mm)	125mm	125mm	170mm	210mm	225mm	240mm
Filled Weight (kg)	2.1	3.8	5.5	6.8	9.2	13.6
Range of Throw (m)	>2	>2	>2	>4	>4	>4
Duration of Discharge (secs)	>6	>9	>9	>9	>15	>15
Working Pressure (at 20°C)	14Bar	14Bar	14Bar	14Bar	14Bar	14Bar
Temperature Range (°C)	- 30/+60	-30/+60	- 30/+60	- 30/+60	-30/+60	-30/+60
BS EN3 Approved	YES	YES	YES	YES	YES	YES
MED Approved	N/A	N/A	N/A	N/A	N/A	N/A
35KV	N/A	N/A	N/A	N/A	N/A	N/A
Pressure Relief Valve	YES	YES	YES	YES	YES	YES
Low Freeze Additive	N/A	N/A	N/A	N/A	N/A	N/A
Part Number	81/02908	81/02900	81/03645	81/03407	81/02901	81/02902
Model Number	PG1A	PG2A	PG3A **	PG4A	PG6A	PG9A





















